



QMFZ2.E235269 Plastics - Component

For enhanced search functionality, please visit UL's iQ™ Family of Databases.
Click on a product designation for complete information.

[Page Bottom](#)

Plastics - Component

[See General Information for Plastics - Component](#)

NAN YA PLASTICS (HUI ZHOU) CORP LTD

E235269

YONGSHI DA DAO

SHI WAN TOWN

HUIZHOU, GUANGDONG 516000 CHINA

									H	D	
		Min.		H	H	R T I			V	4	C
		Thk	Flame	W	A	Elec	Mech		T	9	T
Material Dsg	Color	mm	Class	I	I		Imp	Str	R	5	I
Acrylonitrile Butadiene Styrene/Polybutylene Terephthalate (ABS/PBT), furnished as pellets.											
1602	ALL	1.5	HB	-	-	60	60	60	-	-	-
Acrylonitrile Butadiene Styrene/Polycarbonate (ABS/PC), furnished as pellets.											
5612	ALL	1.5	HB	-	-	60	60	60	2	7	2
		3.0	HB	3	0	60	60	60			
5712(f1)	ALL	1.5	V-0	2	1	100	85	90	1	6	2
		3.0	V-0	1	0	100	85	90			
571P	ALL	1.5	V-0	-	-	60	60	60	-	-	-
		3.3	V-0	-	-	60	60	60			
571PG(e)	ALL	1.5-1.65	V-0	-	-	60	60	60	-	-	-
5722(f2)	ALL	1.5	V-0	3	0	100	90	100	3	7	0
		3.2	V-0	2	0	100	90	100			
Polyamide 6 (PA6), furnished as pellets.											
2110	ALL	0.75	V-2	4	0	140	75	75	0	5	0
		1.5	V-2	3	0	140	80	85			
		3.0	V-2	3	0	140	80	85			
2200M6	ALL	0.75	HB	-	-	65	65	65	0	5	0
		3.0	HB	1	0	65	65	65			
2200M9	ALL	1.5	HB	-	-	65	65	65	-	-	-
2210G(c)	ALL	0.75	HB	4	0	120	75	75	0	6	0
		1.5	HB	3	0	120	80	85			
		3.0	HB	3	0	120	80	85			
2210G2	ALL	0.75	HB	4	0	130	75	75	0	6	0
		1.5	HB	3	0	130	80	85			

		3.0	HB	3	0	130	80	85			
2210G3	ALL	0.75	HB	3	0	130	100	115	0	6	0
		1.5	HB	0	0	130	110	120			
		3.0	HB	0	0	130	110	120			
2210G4	ALL	0.75	HB	4	0	120	100	115	0	6	0
		1.5	HB	3	0	120	100	115			
		3.0	HB	0	0	120	100	115			
2210G5	ALL	0.75	HB	4	0	120	100	115	0	6	0
		1.5	HB	3	0	120	100	115			
		3.0	HB	0	0	120	100	115			
2210G6	ALL	0.75	HB	4	0	120	100	115	0	6	0
		1.5	HB	2	0	120	100	115			
		3.0	HB	0	0	120	100	115			
2210G7	ALL	0.75	HB	4	0	120	100	115	0	6	0
		1.5	HB	3	0	120	100	115			
		3.0	HB	3	0	120	100	115			
2210G8	ALL	0.75	HB	4	0	120	100	115	0	6	0
		1.5	HB	3	0	120	100	115			
		3.0	HB	3	0	120	100	115			
2210G9	ALL	0.75	HB	3	0	120	100	115	0	6	0
		1.5	HB	1	0	120	100	115			
		3.0	HB	0	0	120	100	115			
2310	ALL	0.75	V-0	4	0	140	90	110	0	6	0
		1.5	V-0	3	0	140	100	115			
		3.0	V-0	2	0	140	100	115			
Polyamide 66 (PA66), with glass fiber reinforced, furnished as pellets.											
640PG(k)	ALL	0.75	V-0	0	0	115	95	95	2	6	1
		3.0	V-0	0	0	115	95	95			
640PG1	ALL	0.75	V-0	0	0	115	95	95	2	5	1
		3.0	V-0	0	0	115	95	95			
640PG8	ALL	0.75	V-0	0	0	120	110	110	2	6	0
		3.0	V-0	0	0	120	110	110			
641PG(k)	ALL	3.0-3.3	V-0	0	0	65	65	65	2	5	0
Polyamide 66 (PA66), furnished as pellets.											
6110	ALL	0.75	V-2	4	0	130	80	85	0	6	0
		1.5	V-2	3	0	130	80	85			
		3.0	V-2	2	0	130	85	85			
6210G(c)	ALL	0.75	HB	4	0	105	80	85	0	6	0
		1.5	HB	2	0	105	80	85			
		3.0	HB	0	0	105	85	85			
6210G2	ALL	0.75	HB	4	0	120	80	85	0	6	0
		1.5	HB	3	0	120	80	85			

		3.0	HB	2	0	120	85	85			
6210G3	ALL	0.75	HB	4	0	120	100	100	0	6	0
		1.5	HB	2	0	120	100	100			
		3.0	HB	0	0	120	105	105			
6210G4	ALL	0.75	HB	4	0	115	100	100	0	6	0
		1.5	HB	2	0	115	100	100			
		3.0	HB	0	0	115	105	105			
6210G5	ALL	0.75	HB	4	0	115	100	100	0	6	0
		1.5	HB	2	0	115	100	100			
		3.0	HB	0	0	115	105	105			
6210G6	ALL	0.75	HB	2	0	115	100	105	0	6	0
		1.5	HB	1	0	115	100	105			
		3.0	HB	0	0	115	105	105			
6210G7	ALL	0.75	HB	3	0	105	100	105	0	6	0
		1.5	HB	1	0	105	100	105			
		3.0	HB	0	0	105	105	105			
6210G8	ALL	0.75	HB	3	0	105	100	105	0	6	0
		1.5	HB	1	0	105	100	105			
		3.0	HB	0	0	105	105	105			
6210G9	ALL	0.75	HB	3	0	105	105	105	0	6	0
		1.5	HB	1	0	105	105	105			
		3.0	HB	0	0	105	105	105			
6300	ALL	0.2	V-0	4	0	65	65	65	0	5	0
		3.0	V-0	1	0	65	65	65			
6310	ALL	0.75	V-0	3	0	120	105	105	1	7	2
		1.5	V-0	3	0	120	105	105			
		3.0	V-0	1	0	120	105	105			
6400G5	ALL	3.0	V-0	-	-	65	65	65	-	-	-
6401G(a)	ALL	3.0	V-0	-	-	65	65	65	-	-	-
6401G1	NC	1.5	V-1	-	-	65	65	65	-	-	-
	RD	1.5	V-2	-	-	65	65	65			
	WT, BK	1.5	V-0	-	-	65	65	65			
	ALL	3.0	V-0	-	-	65	65	65			
6401G6	ALL	1.5	V-0	-	-	65	65	65	-	-	-
6410G(d)	ALL	0.75	V-0	3	0	120	105	105	1	7	2
		1.5	V-0	3	0	120	105	105			
		3.0	V-0	1	0	120	105	105			
6410G3	ALL	0.75	V-0	3	0	120	105	105	1	6	2
		1.5	V-0	3	0	120	105	105			
		3.0	V-0	1	0	120	105	105			
6410G4	ALL	0.75	V-0	3	0	120	105	105	1	6	2
		1.5	V-0	3	0	120	105	105			

		3.0	V-0	1	0	120	105	105			
6410G5	ALL	0.75	V-0	0	0	130	115	120	1	6	2
		1.5	V-0	0	0	130	115	120			
		3.0	V-0	0	0	130	115	120			
6512	ALL	0.8	HB	-	-	65	65	65	-	-	-
		3.2	HB	-	-	65	65	65			
Polybutylene Terephthalate (PBT), 30% glass reinforced, furnished as pellets.											
1408G6	ALL	0.4-0.44	V-0	0	0	140	75	130	2	7	2
Polybutylene Terephthalate (PBT), with glass fiber reinforced, furnished as pellets.											
140PG(m)	ALL	0.75	V-0	0	0	130	75	130	4	5	1
		3.0	V-0	0	0	130	75	140			
140PG3	ALL	0.75	V-0	0	0	130	75	130	4	5	1
		3.0	V-0	0	0	130	75	140			
140PG6	ALL	0.75	V-0	0	0	130	75	130	4	5	0
		3.0	V-0	0	0	130	75	140			
141PG(b)	ALL	3.0-3.3	V-0	-	-	75	75	75	-	-	-
Polybutylene Terephthalate (PBT), furnished as pellets.											
1100F, 1101FA, 1101FB, 1110F, 1111FA, 1111FB											
	ALL	0.83	HB	4	1	130	75	140	0	5	0
		1.5	HB	4	0	130	120	140			
		3.0	HB	3	0	130	120	140			
		6.0	HB	1	0	130	120	140			
1210G3	WT, BK	0.84	HB	4	3	130	75	140	1	5	-
	ALL	1.5	HB	4	0	130	120	140			
		3.0	HB	3	0	130	120	140			
		6.0	HB	1	0	130	120	140			
1210G6	WT, BK	0.81	HB	2	3	140	120	140	1	5	1
	ALL	1.5	HB	1	0	140	120	140			
		3.0	HB	1	0	140	120	140			
		6.0	HB	0	0	140	120	140			
1216G9	ALL	0.81	HB	-	-	75	75	75	-	-	-
1300	ALL	0.81	V-0	4	0	105	105	105	3	6	3
		1.5	V-0	3	0	115	105	115			
		3.0	V-0	2	0	115	105	115			
		6.0	V-0	1	0	115	105	115			
1300A	ALL	0.75	V-0	4	0	75	75	75	3	7	2
		1.5	V-0	3	0	75	75	75			
		3.0	V-0	2	0	75	75	75			
1307	ALL	0.75	V-0	4	2	140	120	140	2	6	3
		1.5	V-0	4	1	140	120	140			
		3.0	V-0	2	2	140	120	140			
1400G(a)	ALL	0.71	V-0	4	4	130	115	120	3	6	3

		1.5	V-0	3	0	130	115	120			
		3.0	V-0	2	0	130	120	125			
		6.0	V-0	1	0	130	120	125			
1400G1	ALL	0.71	V-0	4	4	140	130	140	3	6	1
		1.5	V-0	3	0	140	130	140			
		3.0	V-0	2	0	140	130	140			
		6.0	V-0	1	0	140	130	140			
1400G2	ALL	0.71	V-0	4	4	130	115	120	3	6	3
		1.5	V-0	3	0	130	115	120			
		3.0	V-0	2	0	130	120	125			
		6.0	V-0	1	0	130	120	125			
1400G3	ALL	0.71	V-0	4	4	130	115	120	3	6	3
		1.5	V-0	3	0	130	115	120			
		3.0	V-0	2	0	130	120	125			
		6.0	V-0	1	0	130	120	125			
1400G4	ALL	0.71	V-0	4	4	130	115	120	3	6	3
		1.5	V-0	3	0	130	115	120			
		3.0	V-0	2	0	130	120	125			
		6.0	V-0	1	0	130	120	125			
1400G6	ALL	0.71	V-0	3	4	130	115	120	2	6	3
		1.5	V-0	2	0	130	115	120			
		3.0	V-0, 5VA	2	0	130	120	125			
		6.0	V-0	0	0	130	120	125			
1401G(b)	ALL	1.5	V-0	-	-	75	75	75	-	-	-
1401G3	ALL	1.5	V-0	-	-	75	75	75	-	-	-
1401G6	ALL	1.5	V-0	-	-	75	75	75	-	-	-
1402G(a)	ALL	0.75	V-0	4	0	140	130	140	2	6	3
		1.5	V-0	3	0	140	130	140			
		3.0	V-0	3	0	140	130	140			
1402G1	ALL	0.75	V-0	4	0	140	130	140	2	6	3
		1.5	V-0	3	0	140	130	140			
		3.0	V-0	3	0	140	130	140			
1402G2	ALL	0.75	V-0	4	0	140	130	140	2	6	3
		1.5	V-0	3	0	140	130	140			
		3.0	V-0	3	0	140	130	140			
1402G3	ALL	0.75	V-0	4	0	140	130	140	2	6	3
		1.5	V-0	3	0	140	130	140			
		3.0	V-0	3	0	140	130	140			
1402G4	ALL	0.75	V-0	4	0	140	130	140	2	6	3
		1.5	V-0	3	0	140	130	140			
		3.0	V-0	3	0	140	130	140			
1402G6	ALL	0.75	V-0	3	0	140	130	150	1	5	3

		1.5	V-0	2	0	140	130	150			
		3.0	V-0	1	0	140	130	150			
1403G(a)	ALL	0.75	V-0	4	0	130	130	140	2	6	3
		1.5	V-0	3	0	130	130	140			
		3.0	V-0	2	0	130	130	140			
1403G1	ALL	0.75	V-0	4	0	140	130	140	2	6	3
		1.5	V-0	3	0	140	130	140			
		3.0	V-0	2	0	140	130	140			
1403G2	ALL	0.75	V-0	4	0	130	130	140	2	6	3
		1.5	V-0	3	0	130	130	140			
		3.0	V-0	2	0	130	130	140			
1403G3	ALL	0.75	V-0	4	0	130	130	140	2	6	3
		1.5	V-0	3	0	130	130	140			
		3.0	V-0	2	0	130	130	140			
1403G4	ALL	0.75	V-0	4	0	130	130	140	2	6	3
		1.5	V-0	3	0	130	130	140			
		3.0	V-0	2	0	130	130	140			
1403G6	ALL	0.75	V-0	3	0	130	130	140	1	6	2
		1.5	V-0	2	0	130	130	140			
		3.0	V-0	2	0	130	130	140			
1403G9	ALL	0.75	V-0	-	-	75	75	75	-	-	-
1406G6	ALL	0.75	V-0	-	-	-	-	-	-	-	-
1406G6A	ALL	1.6	V-0	2	4	75	75	75	2	5	3
		3.0	V-0	0	4	75	75	75			
140RG(b)	BK	0.85	V-0	-	-	75	75	75	-	-	-
		3.2	V-0	-	-	75	75	75			
1410G3	ALL	3.0	V-0	-	-	75	75	75	-	-	-
1410G6	ALL	3.0	V-0	-	-	75	75	75	-	-	-
1512	ALL	0.75	HB	4	0	75	75	75	0	4	0
		3.0	HB	2	0	75	75	75			
1516G9	ALL	0.81	HB	-	-	75	75	75	-	-	-
1519G6	ALL	0.81	HB	-	-	75	75	75	-	-	-
Polybutylene Terephthalate/Polycarbonate (PBT/PC), furnished as pellets.											
5312	ALL	1.5	V-0	2	0	75	75	75	4	6	2
		3.0	V-0	1	0	75	75	75			
5502	ALL	1.6-1.8	HB	-	-	75	75	75	-	-	-
Polycarbonate (PC), glass reinforced, furnished as pellets.											
5420G(N)	ALL	1.5	V-0	2	0	80	80	80	4	6	3
		3.0	V-0	1	0	80	80	80			
5420G2	ALL	1.5	V-0	2	0	80	80	80	4	6	3
		3.0	V-0	1	0	80	80	80			
5420G6	ALL	1.5	V-0	1	0	80	80	80	4	6	3

		3.0	V-0	1	0	80	80	80			
Polycarbonate (PC), furnished as pellets.											
5110	ALL	1.5	V-2	3	3	120	110	125	0	5	3
		3.0	V-2	2	3	120	110	125			
5210G2	ALL	1.5	V-0	-	-	-	-	-	-	-	-
		3.0	V-0	-	-	-	-	-			
5210G3	ALL	1.5	V-0	-	-	-	-	-	-	-	-
		3.0	V-0	-	-	-	-	-			
5210G4	ALL	1.5	V-0	-	-	-	-	-	-	-	-
		3.0	V-0	-	-	-	-	-			
5210G5	ALL	1.5	V-0	-	-	-	-	-	-	-	-
		3.0	V-0	-	-	-	-	-			
5210G6	ALL	1.5	V-0	-	-	-	-	-	-	-	-
		3.0	V-0	-	-	-	-	-			
5310	ALL	1.5	V-2	3	4	120	100	115	0	5	3
		3.0	V-0	2	4	120	105	115			
531P	ALL	1.5-1.65	V-0	2	0	105	105	105	3	6	3
540PG(e)	ALL	1.5-1.65	V-0	2	0	80	80	80	3	6	3
5410G(e)	ALL	0.4	HB	-	-	80	80	80	4	5	3
		1.5	V-2	3	4	120	95	115			
		3.0	V-0	2	4	120	105	115			
5410G1	ALL	0.4	HB	-	-	80	80	80	4	5	3
		1.5	V-0	3	4	120	95	115			
		3.0	V-0	2	4	120	105	115			
5410G2	ALL	0.4	HB	-	-	80	80	80	4	5	3
		1.5	V-0	2	4	120	95	115			
		3.0	V-0	1	4	120	105	115			
5410G3	ALL	0.4	HB	-	-	80	80	80	4	5	3
		1.5	V-0	2	4	120	95	115			
		3.0	V-0	1	4	120	105	115			
5410G4	ALL	0.4	HB	-	-	80	80	80	4	5	3
		1.5	V-0	2	4	120	95	115			
		3.0	V-0	1	4	120	105	115			
5410G5	ALL	0.4	HB	-	-	80	80	80	4	5	3
		1.5	V-0	2	4	120	95	115			
		3.0	V-0	1	4	120	105	115			
5410G6	ALL	0.4	HB	-	-	80	80	80	0	5	3
		1.5	V-0	0	4	120	120	130			
		3.0	V-0	1	4	120	120	130			
5410GE(h)	ALL	1.5	V-0	-	-	80	80	80	-	-	-
Polyethylene Terephthalate (PET), glass reinforced, furnished as pellets.											
4210G(g)	ALL	1.6-1.8	HB	2	0	75	75	75	2	6	2

4410G(g)	BK	0.75	V-0	0	3	150	130	130	1	6	4
		1.5	V-0	0	3	150	130	130			
		3.0	V-0	0	3	150	150	150			
4410G3	BK	0.75	V-0	0	0	150	130	130	0	6	3
		1.5	V-0	0	0	150	130	130			
		3.0	V-0	0	0	150	150	150			
4410G4	BK	0.75	V-0	0	3	150	130	130	0	6	3
		1.5	V-0	0	3	150	130	130			
		3.0	V-0	0	2	150	150	150			
4410G5	BK	0.75	V-0	0	3	150	130	130	0	6	3
		1.5	V-0	0	3	150	130	130			
		3.0	V-0	0	2	150	150	150			
4410G6	ALL	0.75	V-0	0	3	150	130	130	0	6	2
		1.5	V-0	0	3	150	140	150			
		3.0	V-0	0	2	150	150	150			
4410G7	BK	0.75	V-0	0	3	150	130	130	1	6	4
		1.5	V-0	0	3	150	140	150			
		3.0	V-0	0	3	150	150	150			
4410G8	BK	0.75	V-0	0	3	150	130	130	1	6	4
		1.5	V-0	0	3	150	140	150			
		3.0	V-0	0	3	150	150	150			
4410G9	BK	0.75	V-0	0	3	150	140	150	1	5	4
		1.5	V-0	0	3	150	140	150			
		3.0	V-0	0	3	150	150	150			
Polyphenylene Ether (PPE), with glass fiber reinforced, furnished as pellets.											
971PG(N)	WT	0.75	V-1	0	0	65	65	65	4	6	4
	NC, RD, BK	0.75	V-0	0	0	65	65	65			
	ALL	3.0	V-0	0	0	65	65	65			
Polypropylene (PP), glass reinforced, furnished as pellets.											
3219M(j)	ALL	1.5	HB	-	-	110	65	110	-	-	-
		3.0	HB	-	-	110	65	110			
3219M3	ALL	1.5	HB	-	-	110	65	110	-	-	-
		3.0	HB	-	-	110	65	110			
3219M8	ALL	1.5	HB	-	-	115	65	115	-	-	-
		3.0	HB	-	-	115	65	115			
Polypropylene (PP), furnished as pellets.											
3210T(i)	ALL	1.5	HB	-	-	65	65	65	-	-	-
		3.0	HB	-	-	65	65	65			
3307(f1)	ALL	0.8	V-0	4	0	110	110	110	0	5	0
		1.5	V-0	3	0	110	110	110			
		3.0	V-0	2	0	110	110	110			
3317A	ALL	0.35-0.39	V-0	-	-	65	65	65	-	-	-

3410G(j)	ALL	3.2-3.5	V-0	-	-	65	65	65	-	-	-
Polypropylene (PP), furnished as pellets, sheets.											
3117(f1)	ALL	1.5	HB	3	0	125	125	125	0	4	0
		3.0	HB	2	0	125	125	125			
3210G(e)	ALL	0.75	HB	4	3	65	65	65	0	6	0
		1.5	HB	3	1	65	65	65			
		3.0	HB	2	0	65	65	65			
3210G4	ALL	0.75	HB	3	3	65	65	65	0	6	0
		1.5	HB	3	0	65	65	65			
		3.0	HB	2	0	65	65	65			
3210G5	ALL	0.75	HB	3	3	65	65	65	0	6	0
		1.5	HB	3	0	65	65	65			
		3.0	HB	2	0	65	65	65			
3210G6	ALL	0.75	HB	2	3	65	65	65	0	5	0
		1.5	HB	1	0	65	65	65			
		3.0	HB	0	0	65	65	65			
3310	ALL	0.75	V-2	4	0	110	65	65	0	4	0
		1.5-1.7	V-2	4	0	110	110	110			
3317(f1)	ALL	0.75	V-0	4	2	115	115	115	0	6	0
		1.5	V-0	3	1	115	115	115			
		3.0	V-0	2	0	115	115	115			
3410T8	ALL	0.8	V-2	-	-	65	65	65	-	-	-
		1.6	V-2	-	-	65	65	65			
		3.1	V-2	-	-	65	65	65			
Polypropylene (PP), furnished as pellets,sheets.											
3210G1	ALL	0.75	HB	4	3	65	65	65	0	6	0
		1.5	HB	3	1	65	65	65			
		3.0	HB	2	0	65	65	65			

(a) - May be followed by a number 1-6 indicating glass-fiber content between 5-30%

(b) - May be followed by a number or letter indicating glass fiber content 15-30%

(c) - May be followed by a letter indicating glass fiber content 1-45%

(d) - May be followed by a letter indicating glass fiber content 1-25%.

(e) - May be followed by a letter between 1-6 indicating glass-fibercontent between 1-30%

(f1) - Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water Exposure and Immersion in accordance with UL 746C.

(f2) - Subjected to one or more of the following tests: Ultraviolet Light, Water Exposure or Immersion in accordance with UL 746C, where the acceptability for outdoor use is to be determined by UL Subjected to one or more of the following tests: Ultraviolet Light, Water Exposure or Immersion in accordance with UL 746C, where the acceptability for outdoor use is to be determined by UL.

(g) - May be followed by a number 3 - 9 indicating glass-fiber content between 15 - 45%

(h) - May be followed by a letter indicating glass fiber content 1-50%

(i) - May be followed by a number between 2-8 indicating Talcum power contest 10-40%

(j) - May be followed by a number between 3-8 indicating glass fiber contest 15-40%.

(k) - May be followed by a letter indicating glass fiber content between 5~40%

(m) - May be followed by a letter or number indicating glass fiber content between 15 and 30 percent, except 15% and 30%

(N) - May be followed by a letter indicating glass-fiber content between 10~30%

Marking: Company name and material designation on container, wrapper or finished part.

Last Updated on 2016-01-21

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2016 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2016 UL LLC".