

# Fair-Rite P/N **2773001112**

**73 Material Grade**

**Nominal Chemical Composition**

<u>Compound</u>	<u>CAS Number</u>	<u>wt %</u>	Wt of core (g)= <b>0.219</b>	
Fe2O3	1309-37-1	67	0.1467	Compound Weight (g) Breakdown of 73 Material
ZnO	1314-13-2	14	0.0307	
MnO	1344-43-0	19	0.0416	

## **Pb- Free Plated Round Cu Wire**

<u>Element</u>	<u>CAS Number</u>	<u>wt%</u>	Wt of wire (g)= <b>0.181</b>	
Cu	7440-50-8	94.4	0.17086	Element Weight (g) Breakdown of Pb- Free Plated Round Cu Wire
Plating:				
Ni	7440-02-0	0.9	0.00163	
Sn	7440-31-5	4.7	0.00851	

## **Calculated Maximum Levels of RoHS Restricted Substances Present in 73 Material Grade**

<u>Impurity Substance</u>	<u>RoHS Threshold (ppm)</u>	<u>ppm</u>	Wt of core (g)= <b>0.219</b>	
Cr+6	1000	0.00	0	RoHS Impurity Substance Weight (g) Breakdown of 73 Material
<b>Cd</b>	100	<b>3.70</b>	8.103E-07	
<b>Hg</b>	1000	<b>0.10</b>	2.19E-08	
<b>Pb</b>	1000	<b>8.25</b>	1.80675E-06	
PBB	1000	0.00	0	
PBDE	1000	0.00	0	

Supporting notes:

1. P/N 2773001112 consists of:
  - a core 73 Material Grade
  - b wire Pb- Free Plated Round Cu Wire
2. Moisture Sensitivity Level (MSL)= 1
3. Max Reflow Temp= 260 degC
4. Max Time at Max Reflow Temp= 40 sec
5. RoHS 6/6 Compliant Terminations/ Wire are backwards compatible with standard Soldering Processes
6. RoHS Conversion Date= 1/1/2005
7. RoHS Compliance Marking is Contained on Shipping Labels